Den Braven Sealants by

P.O. Box 194, 4900 AD Oosterhout, Denariusstraat 11, 4903 RC Oosterhout, The Netherlands Telephone +31 (0) 162-491000, Fax General +31 (0) 162-451217, E-Mail: Info@denbraven.nl



Zwaluw Montagefix-SBR

Reference 6.11 Grade 611S9521 04-12-2007 Date Replaces previous sheet

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product name Zwaluw Montagefix-SBR Adhesive for the building industry. Use of the product

Supplier See above

+31 (0) 413-268716 if no answer +31 (0) 161-451909 (after working hours) Emergency phone number

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization : Mixture based on rubber, resin, solvent, additives and fillers.

<u>Hazardous ingredients $\geq 1\%$</u>	: <u>CAS</u>	<u>Einecs</u>	Weight	<u>Danger</u>	<u>Risk</u>
and toxic ingredients $\geq 0.1\%$	<u>Number</u>	<u>Number</u>	<u>%</u>	<u>Symbol</u>	<u>Phrases</u>
Acetone Mixed Aliphatic Hydrocarbons	67-64-1	200-662-2	1-5	F, Xi	11-36-66-67
	64742-49-0	265-151-9	20-25	F. Xn. N	11-38-51/53-65-67

3. HAZARDS INDENTIFICATION

: Highly flammable. Potential health effects

Irritating to skin.

Vapours may cause drowsiness and dizziness

4. FIRST AID MEASURES

In case of contact flush eyes immediately with plenty of water for at least 15 minutes. Eyes

Lift eyelids and rinse well underneath them. Get medical attention if irritation persists.

Mouth (ingestion) Rinse mouth with water several times. Consult a physician and show this Safety Data Sheet.

Lungs (inhalation) Fresh air and rest. Get medical attention if complaint persists.

Remove completely with a dry cloth or paper towel, before washing with detergent and water. Skin

Get medical attention if irritation persists.

Remove polluted clothing Clothes

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : CO₂, powder, foam and water spray.

Unsuitable extinguishing media Unknown.

Wear protective clothing and breathing apparatus. Special fire fighting procedures

6. ACCIDENTAL RELEASE MEASURES

Keep away from drains and watercourses. **Environmental precautions**

Clean up procedures Wipe, scrape or soak up in inert material and put in a container for disposal.

Wear proper protective equipment as described in the 'eye and skin protection' section of chapter 8. Personal precautions

7. HANDLING AND STORAGE

Handling Handle in well-ventilated area. Avoid contact with skin, eyes and do not swallow.

Storage Store in closed packing between 5°C and 25°C away from direct sunlight and other sources of heat.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit : MAC Acetone 1210 mg/m^3

> MAC Mixed Aliphatic Hydrocarbons 1000 mg/m³

Respiratory protection Avoid breathing the vapour. Maintain good ventilation. Eye and skin protection Avoid contact with skin and eyes. Wear safety glasses.

When using do not eat, drink or smoke. Wash hands after work and before breaks. **Industrial hygiene**

Don't rub eyes with dirty hands.

Zwaluw Montagefix-SBR

Grade: 611S9521

SAFETY DATA SHEET

9. PHYSICAL AND CHEMICAL PROPERTIES

: -35 Physical state paste Flash point $^{\circ}C$ Colour Lower explosion limit vol-% beige 0,6 Odour solvent Upper explosion limit 13 vol-% 200 Density (water=1) 1.14 g/ml Ignition temperature $^{\circ}C$ pH (water=7) NA Vapour pressure <250 mbar Mixable with water Boiling point (water =100) 56 No :

Freezing point (water = 100) : NA °C Mixable with water : No Mixable with organic solvents : Yes

VOC-content : 26 Weight-%

10. STABILITY AND REACTIVITY

Hazardous decomposition products: In case of fire: CO.

Materials to avoid: Strong oxidizing agents.

Conditions to avoid : Keep away from sources of ignition.

11. TOXICOLOGICAL INFORMATION

 Product information
 Acetone
 Mixed Aliphatic Hydrocarbons

 Acute oral LD50 (mg/kg)
 : 5800 (rat)
 >5000 (rat)

 Acute dermal LD50 (mg/kg)
 : 5500 (rat)
 unknown

 Acute inhalation LC50 (mg/l)
 : unknown
 unknown

Other information: Repeated or prolonged contact with the skin may cause dermatitis.

For information on hazardous substances see 'chapter' 2.

12. ECOLOGICAL INFORMATION

Avoid uncured product will come in the environment.

Degradability : Unknown.

Ecotoxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

WGK (Germany) : 1

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with federal, state and local legislation.

14. TRANSPORT INFORMATION

By sea according IMDG-Code
By land according ADR

: Class: 3, Packing group: II, EmS: F-E, S-D, Limited Quantity: 5ℓ/30kg.
: Class: 3, Classification code: F1, Packing group: II, Limited Quantity: LQ6.

By air according ICAO/IATA-DGR : Class: 3, Packing group: II.

UN-number : 1133 Proper shipping name : Adhesives

15. REGULATORY INFORMATION

To the labelling requirements of EC Directives 67/548/EC and 1999/45/EC:

 $\textbf{Danger symbol} \hspace{1.5cm} \textbf{:} \hspace{0.2cm} \textbf{F} \hspace{0.2cm} \textbf{Highly flammable}, \textbf{Xi} \hspace{0.2cm} \textbf{Irritant}$

Contains : Not applicable.
R-phrases : 38 Irritating to skin.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

S-phrases

67 Vapours may cause drowsiness and dizziness.

Keep out of reach of children.

16 Keep away from sources of ignition – no smoking.

23 Do not breathe vapour.

46 If swallowed seek medical advice immediately and show this container or label.

For DIY user : Tactile warning applicable.

16. OTHER INFORMATION

This product safety data sheet conforms to EC Directive 91/155/EEC as well as its amendments including 2001/58/EC.

This data is offered in good faith as typical values and not as product specifications. No warranty either expressed or implied, is hereby made.

The recommended industrial and safe handling procedures are believed to be generally applicable, each user should review the recommendations in the specific context of the intended use and determine whether they are appropriate.

NA : Not Applicable Unk : Unknown