Reviewed on 25.04.2006

1 Identification of the substance/preparation and of the company/undertaking

· Product details

- · Trade name: 1-Component polyurethane foam B1 quality
- Application of the substance / the preparation 1-Component polyurethane foam in aerosol cans B1 quality
- Manufacturer/Supplier: BÜKA-Chemie GmbH Industriestraße 1-7 D-01936 Schwepnitz
- · Further information obtainable from: Abteilung Umweltschutz
- Information in case of emergency: (49)(0)357976460

2 Composition/information on ingredients

· Chemical characterization

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues Xn; R 20-36/37/38-42/43	25-50%		
CAS: 75-28-5 EINECS: 200-857-2	isobutane F+; R 12	2.5-10%		
CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether F+; R 12	2.5-10%		
CAS: 811-97-2 EINECS: 212-377-0	1,1,1,2-Tetrafluorethan	2.5-10%		
• Additional information: For the wording of the listed risk phrases refer to section 16.				

3 Hazards identification

· Hazard description:



Xn Harmful F+ Extremely flammable

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

R 12 Extremely flammable.

R 20 *Harmful by inhalation.*

R 36/37/38 Irritating to eyes, respiratory system and skin.

R 42/43 May cause sensitisation by inhalation and skin contact.

Contains isocyanates. See information supplied by the manufacturer

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation. Keep out of the reach of children

(Contd. on page 2)

Reviewed on 25.04.2006

(Contd. of page 1)

Trade name: 1-Component polyurethane foam B1 quality

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Additional information:

When transported by motorcar or truck cans have to stand upright in the boot or on the loading space - not in car interior.

Only unreacted formulation or fresh foam is harmful. The blowing agent is extremely flammable.

4 First-aid measures

- General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly. Fresh foam remove or scrape carefully.

- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Call for a doctor immediately.

5 Fire-fighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot Special hazards caused by the substance, its products of combustion or resulting gases:
- Can form explosive gas-air mixtures.
- Formation of toxic gases is possible during heating or in case of fire.

Danger of bursting by heating.

- *Protective equipment:* Mouth respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection:

Do not allow product to reach sewage system or any water course.

· Measures for cleaning/collecting:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Foamed out fresh material should be wetted or covered with moisture absorbing materials (sand, wood shavings, absorbing chemicals) for curing

7 Handling and storage

· Handling:

- · Information for safe handling:
- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

(Contd. on page 3)

Reviewed on 25.04.2006

Trade name: 1-Component polyurethane foam B1 quality

(Contd. of page 2)

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· Storage:

• Requirements to be met by storerooms and receptacles: Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

• Information about storage in one common storage facility: Not required.

- Further information about storage conditions:
- Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

MEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³

Sen; as -NCO

811-97-2 1,1,1,2-Tetrafluorethan

OES Long-term value: 4240 mg/m³, 1000 ppm

115-10-6 dimethyl ether

OES Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm IOELV

• Additional information: The lists valid during the making were used as basis.

· Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

• Respiratory protection:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Recommandation: Polychoropren CR (min. 0,5mm) Nitrile rubber NBR (min. 0,5mm)

(Contd. on page 4)

Reviewed on 25.04.2006

Trade name: 1-Component polyurethane foam B1 quality

(Contd. of page 3)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

General Information	
Form:	Aerosol
Colour:	beige or colored
Odour:	Characteristic
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
Flash point:	Not applicable, as aerosol.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Vapour pressure at 20°C:	6 bar
Density at 20°C:	1.14 g/cm ³
Solubility in / Miscibility with water:	Not miscible or difficult to mix.

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Acute toxicity:

· LD/LC50	values	relevant	for	classification:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	0.49 mg/l (rat)

(Contd. on page 5)

Material Safety Data Sheet According to 2001/58/EC

Printing date 25.04.2006

Reviewed on 25.04.2006

Trade name: 1-Component polyurethane foam B1 quality

(Contd. of page 4)

• Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Irritating effect.

· Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful

Irritant

12 Ecological information

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

13 Disposal considerations

· Product:

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Taking back and recycling of empty cans free of charge in Germany :

PDR Recycling GmbH & Co KG

Am -Alten-Sägewerk 3

D-95349 Thurnau

Free call 0800 783 67 36 Fax 0800 783 67 37

· European waste catalogue

17 06 04 insulation materials other than those mentioned in 17 06 01 and 17 06 03

16 05 04 gases in pressure containers (including halons) containing dangerous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

Land transport ADR/RID (cross-border)

ADR/RID class: 2 5F Gases.
UN-Number: 1950
Packaging group: Hazard label 2.1, LQ2


(Contd. on page 6)

Material Safety Data Sheet According to 2001/58/EC

Printing date 25.04.2006

Reviewed on 25.04.2006

Trade name: 1-Component polyurethane foam B1 quality



15 Regulatory information

• Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

 \cdot Code letter and hazard designation of product:

Xn Harmful

 $F+Extremely\, flammable$

• *Hazard-determining components of labelling: diphenylmethanediisocyanate,isomeres and homologues*

· Risk phrases:

- *12 Extremely flammable.*
- 20 Harmful by inhalation.

36/37/38 Irritating to eyes, respiratory system and skin.

42/43 May cause sensitisation by inhalation and skin contact.

· Safety phrases:

- 2 Keep out of the reach of children.
- 37 Wear suitable gloves.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 28 After contact with skin, wash immediately with plenty of soap and water.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 51 Use only in well-ventilated areas.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

56 Dispose of this material and its container to hazardous or special waste collection point.

· Special labelling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Material Safety Data Sheet According to 2001/58/EC

Printing date 25.04.2006

Reviewed on 25.04.2006

Trade name: 1-Component polyurethane foam B1 quality

(Contd. of page 6)

GF

Keep out of the reach of children

· National regulations:

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

Extremely flammable. 12

20 Harmful by inhalation.

36/37/38 Irritating to eyes, respiratory system and skin.

42/43 May cause sensitisation by inhalation and skin contact.